CONSTRUCTION PRODUCTS REGULATION (EU) 305/2011
DECLARATION OF PERFORMANCE DoP N°: 002-G

CARL FUHR GmbH & Co. KG
Schlösser und Beschläge

1. Unique identification code of the product type:

Emergency exit devices according to DIN EN 179/BS EN 179

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Panic multipoint locking systems for single-leaf doors	
Locking type	**Certificate of Conformity**
multisafe 870, multitronic 881 – type 3/8/11	**1309-CPR-0421** **0086-CPR-746193**
autosafe 833P, autotronic 834P – type 4	
autosafe 833P as Kindergarten solution – type 4, **autotronic 834P as Kindergarten solution – type 4**	
autosafe 835P/-xxx, autotronic 836P/-xxx – type 10	
multisafe 871 (panic mortise lock)	
autosafe 835P as Kindergarten solution – type 10,	**1309-CPR-0421**
autosafe 837P – type 10	
autosafe 872P – type 13	
Panic multipoint locking systems for double-leaf doors	
autosafe 833P, autotronic 834P – type 4	**1309-CPR-0421** **0086-CPR-746193**
autosafe 835P/-xxx, autotronic 836P/-xxx – type 10	
Panic keep MPGxxx, MPWxxx, **MPWxxx mit Stangenversatz, MPXxxx**	
Panic keep MPB65 xxx	

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen

Emergency exit device with lever handle or push pad operation
for single- and double-leaf doors on escape routes and emergency exits

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11 (5):

CARL FUHR GmbH & Co. KG
Carl-Fuhr-Straße 12
D-42579 Heiligenhaus

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. The PIV Velbert with the DAKKS accreditation number No. 1309 has taken the type test in accordance with the requirements of EN 179:2008 and assessed and verified the constancy of performance according to system 1 and issued the test report.

8. European Technical Assessment:

N/A

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Ability to release (for doors on escape routes)		DIN EN 179:2008 BS EN 179:2008
4.1.2 Release function	≤ 1 sec	
4.1.3 Release operation	The release direction of the device is in and against the direction of the door opening – test passed	
4.1.4 Lever handle design	The device releases the door following a movement of the lever handle/push-pad in a downward rotational direction	
4.1.5 Push-pad design	Test passed	
4.1.6 Double doorset	Test passed	
4.1.8 Exposed edges and corners	≥ 0,5 mm	
4.1.11 Push-pad installation	Z ≤ 250mm	
4.1.12 Lever handle installation	X ≥ 120 mm; Z ≤ 150 mm	
4.1.13 Operating element projection	Category 1 and 2: projection up to 150 mm and up to 100 mm	
4.1.14 Operating element face	V ≥ 18 mm; thickness lever handle ≥ 5 mm	
4.1.15 Lever handle free end	U ≥ 40 mm; W ≤ 100 mm; α ≤ 30°	
4.1.16 Lever handle operating gap	The test block passes freely between the lever handle and the surface of the door.	
4.1.17 Push-pad operating gap	R ≥ 25 mm	
4.1.18 Test rod	The device does not trap the test rod in any position of the lever handle	
4.1.19 Push pad release operation	Push handle passed test.	
4.1.20 Accessible gap	The test-piece does not prevent the correct operation of the lock in any position where it fills accessible spaces. Accessible gap = 20mm	
4.1.21 Door free movement	The device does not include any element impeding the free movement of the door once it is released	
4.1.22 Top vertical bolt	It does not apply to this device	
4.1.24 Keepers	Test passed.	
4.1.25 Keepers dimensions	H ≤ 15mm; M ≤ 45°; P ≤ 3mm	
4.1.27 Door mass and dimensions	870 type 3/8/11, 881 type 3/8/11, 871: Mass ≤ 200 kg, height ≤ 4000 mm, width ≤ 1320 mm Panic keep MPB65xxx: Mass ≤ 200 kg, height ≤ 4000 mm, width ≤ 1600 mm 833P, 834P, - Kindergarten solution, 835P, 836P, -xxx, Panic keep MPWxxx, - mit Stangenversatz, MPGxxx, MPXxxx: Mass ≤ 400 kg, height ≤ 4000 mm, width ≤ 1600 mm	
	837P: Mass ≤ 200 kg, height ≤ 4000 mm, width ≤ 1320 mm 835P - Kindergarten solution, 872P: Mass ≤ 400 kg, height ≤ 4000 mm, width ≤ 1600 mm	DIN EN 179:2008
4.1.28 Outside access device (OAD)	The OAD does not render the panic device inoperable from the inside	DIN EN 179:2008 BS EN 179:2008
4.2.2 Release forces	Type A ≤ 70 N; Type B ≤ 150N	
4.2.7 Security requirements	Grade 2: 1000N; Grade 4: 3000N; Grade 5: 5000N	
Durability of ability to release against aging and degradation (for doors on escape routes)		
4.1.7; 4.2.9 Corrosion resistance	Klasse 3; 96h Type A ≤ 100N; Type B ≤ 220N	
4.1.9 Temperature range	-10°C and +60°C ≤ 50% over the value, if 20°C	
4.1.23; 4.2.6 Covers for vertical rods	It does not apply to this device	
4.1.26 Lubrication	Every 20 000 test cycles without dismantling the device	
4.2.3 Re-engagement force	≤ 50 N	

Essential characteristics	Performance	Harmonised technical specification
4.2.4 Durability	Grade 7: 200 000 test cycles	DIN EN 179:2008 BS EN 179:2008
4.2.5 Abuse resistance-Operating element	Perpendicular pull force ≤ 1 000 N, parallel force ≤ 500 N	
4.2.6 Abuse resistance-Vertical rod	It does not apply to this device	
4.2.8; 4.2.2; 4.1.21 Final examination	The device is released with a force of ≤ 70 N (Type A) resp. 150N (Type B) and the door moves freely once the device is released	
Self closing ability C (for fire/smoke doors on escape routes)		
4.2.3 Re-engagement force	≤ 50N	
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)		
4.2.4 Durability	Grade 7: 200 000 test cycles	
4.2.3 Re-engagement force	≤ 50 N	
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)		
4.1.10 Suitability of emergency exit devices for smoke/fire resisting doorsets	Grade B: suitable ▪ autosafe 835P/-xxx, autotronic 836P/-xxx type 10 ▪ multisafe 870 type 3, type 8, type 11 ▪ multitronic 881 type 3, type 8, type 11 ▪ autosafe 833P type 4, autotronic 834P type 4 ▪ multisafe 871 ▪ Panic keep MPGxxx, MPWxxx, MPWxxx - mit Stangenversatz, MPXxxx Grade 0: not tested ▪ autosafe 833P type 4 Kindergarten solution ▪ autotronic 834P type 4 Kindergarten solution ▪ Panic keep MPB65 xxx	
	Grade B: suitable ▪ autosafe 837P type 10 Grade 0: not tested ▪ autosafe 835P type 10 Kindergarten solution multisafe 872P type 13	DIN EN 179:2008
Control of dangerous substances		DIN EN 179:2008 BS EN 179:2008
4.1.22 Dangerous substances	The materials used in this product do not contain dangerous substances. Nor do they release more of them to the environment than required by any European standard or regulation.	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Andreas Fuhr, Managing Director/Owner
(Name of signatory and position in the company)

Heiligenhaus, 11.11.2025
……
(place and date of issue)

……
(signature)