

# SKG-IKOB PRODUCTCERTIFICATE

## 404.212.06

Date of issue: 20-06-2022



### Certificate holder

Fuhr GmbH & Co KG  
Carl Fuhr Straße 12  
D-42579 Heiligenhaus  
T: +49 (0) 2056 5920  
E: info@fuhr.de  
I: www.fuhr.de



### Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

**cylinder mortice multipointlock wo electromechanical**

delivered under logo / brand:

**FUHR**

delivered under type- and / or article number:

**833 / 834 - type 4 - SKG2**

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A blue ink handwritten signature, appearing to be "ir. H.A.J. van Dartel", written over a light blue horizontal line.

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
info@skgikob.nl  
www.skgikob.nl

# SKG-IKOB PRODUCTCERTIFICATE

Fuhr GmbH & Co KG  
Number: 404.212.06

page 2 of 2

## 1. PRODUCT

cylinder mortice multipointlock wo electromechanical

## PRODUCT TYPE

multipoint lock

## 2. TECHNICAL SPECIFICATION

Operating:	Mechanical and electrical operation
Construction:	1 forend with main lock with latch and square bolt and 2 additional automatic square bolts
System:	self-closing, key or electronic operated lockable by 17 mm profile cylinder OR electronic PZ: 92 mm , BS: 35~80 mm
Material:	forend: steel zinc coated or inox lock cases: steel zinc coated
Dimension:	wood: forend: 1546/2405 mm x (U)20~30x2,7 mm aluminium: forend: 1546/2405 mm x (U)16~30x2,7 mm lock cases: 210xBS+18x15 mm / 130x45x16 mm
Fixing:	forend in hard wood 4x40 mm, in soft wood 4x50 mm forend in Aluminium: M5x16 in nuths
Intended use:	wood, metal, door-inward-opening, door-outward-opening in combination with FUHR box keepers or keeperstrip: wood: 404.612.06 metal: 404.613.02

## 3. DELIVERY

The delivery includes an installation instruction:  
1-0800-007 OF 1-0800-006

## 4. PERFORMANCES

A cylinder mortice multipointlock wo electromechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this cylinder mortice multipointlock w/o electromechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this cylinder mortice multipointlock w/o electromechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).