

UKCA Certificate of Constancy of Performance

This is to certify that:

Carl Fuhr GmbH & Co. KG
Carl-Fuhr-Str. 12
Heiligenhaus
Nordrhein-Westfalen
42579
Germany

Holds Certificate Number:

0086 CPR 746195

In respect of:

BS EN 1125:2008 – Autosafe, Autotronic, Multisafe and Multitronic Series Panic Exit Devices. Mechanically operated by either a horizontal push-bar or a horizontal touch-bar, specifically designed for use in a panic situation on escape routes.

In compliance with the Regulation (UK) Statutory Instrument 2019 No 465 of the United Kingdom Parliament (Construction Products (Amendment etc.) (EU Exit) Regulations or CPR), this certificate applies to the above construction product. This certificate attests that all the provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the above standard(s) under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product. This certificate was first issued on the date below and will remain valid as long as neither the designated standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the approved product certification body.

For and on behalf of BSI, an Approved Body for the above Regulation (Approved Body Number 0086):

Frank Lee, Product Certification Technical and Compliance Director

First Issued: 2021-07-12

Effective Date: 2021-07-12

Latest Issue: 2021-07-12

Page: 1 of 7

...making excellence a habit.™

UKCA Certificate of Constancy of Performance

No. 0086 CPR 746195

BS EN 1125:2008 - Building hardware – Panic exit devices operated by a horizontal bar, for use on escape routes.

Table 1: Requirements for panic exit devices in line with BS EN 1125:2008 (to be read in conjunction with Tables 2 & 3)		
Product:	Panic exit devices operated by a horizontal bar as covered by the scope of BS EN 1125:2008.	
Intended use:	For doors on escape routes.	
Essential characteristics	Clauses within BS EN 1125:2008	Compliance
		Models 1 - 24
Ability to release (for doors on escape routes)	4.2.1	Pass
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1	Pass
Self closing ability C (for fire/smoke doors on escape routes)	4.2.1	Pass
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1	Pass
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	4.2.1	Pass
Control of Dangerous substances	4.1.25	Pass
Note:	<i>This details only those essential characteristics as required in the ZA Annex of BS EN 1125:2008 and applicable to a horizontal bar operation.</i>	

First Issued: 2021-07-12

Effective Date: 2021-07-12

Latest Issue: 2021-07-12

Page: 2 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 746195

BS EN 1125:2008 - Building hardware – Panic exit devices operated by a horizontal bar, for use on escape routes.

Table 2: Product Information – Panic Exit Devices not approved for use on fire /smoke door assemblies.			
No	Description	Additional Information	Model
1	Panic exit device	Automatic multipoint locking system with anti-panic function *	Autosafe 833P Kindergarten Solution
2	Panic exit device	Electronic automatic multipoint locking system with anti-panic function *	Autotronic 834P Kindergarten Solution
3	Panic exit device	Automatic multipoint locking system with anti-panic function	Autosafe 835P Typ 10
4	Panic exit device	Electronic automatic multipoint locking system with anti-panic function	Autotronic 836P Typ 10
5	Panic exit device	Automatic multipoint locking system with anti-panic function	Autosafe 835P Typ 10 Version 2-leaf
6	Panic exit device	Electronic automatic multipoint locking system with anti-panic function	Autotronic 836P Typ 10 Version 2-leaf
7	Panic exit device	Automatic multipoint locking system with anti-panic function	Autosafe 835P xxx Typ 10
8	Panic exit device	Electronic automatic multipoint locking system with anti-panic function	Autotronic 836P xxx Typ 10
9	Panic exit device	Automatic multipoint locking system with anti-panic function	Autosafe 835P xxx Typ 10 Version 2-leaf
10	Panic exit device	Electronic automatic multipoint locking system with anti-panic function	Autotronic 836P xxx Typ 10 Version 2-leaf

First Issued: 2021-07-12

Effective Date: 2021-07-12

Latest Issue: 2021-07-12

Page: 3 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 746195

BS EN 1125:2008 - Building hardware – Panic exit devices operated by a horizontal bar, for use on escape routes.

Table 2: Product Information – Panic Exit Devices not approved for use on fire /smoke door assemblies (continued....)			
No	Description	Additional Information	Model
11	Panic exit device	Inactiv-leaf shutter incl. locking set (xxxxx stands for profile specific item number)	Multisafe 870 MP352xxxxx MP402xxxxx MP452xxxxx MP552xxxxx MP652xxxxx
12	Panic exit device	Multipoint locking system with anti-panic function	Multisafe 870 Typ 8 Version 2-leaf
13	Panic exit device	Electronic multipoint locking system with anti-panic function	Multitronic 881 Typ 8 Version 2-leaf
14	Panic exit device	Anti-panic conter box for inactive-leaf of aluminium steel, wood and plastic doors (x stands for backset / forend sizes dependent item number)	MPB65 xxx
Note	<i>Panic exit devices detailed in table 2 have conformed to the requirements of BS EN 1125:2008, Table 1: Performance characteristics and compliance criteria.</i>		
Note*	<i>Handle Height 850mm</i>		

First Issued: 2021-07-12

Effective Date: 2021-07-12

Latest Issue: 2021-07-12

Page: 4 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 746195

BS EN 1125:2008 - Building hardware – Panic exit devices operated by a horizontal bar, for use on escape routes.

Table 3: Product Information – Panic Exit Devices suitable for use on fire and smoke door assemblies.

No	Description	Additional Information	Model
15	Panic exit device	Automatic multipoint locking system with anti-panic function	Autosafe 833P Typ 4
16	Panic exit device	Automatic multipoint locking system with anti-panic function	Autosafe 833P Typ 4 Version 2-leaf
17	Panic exit device	Electronic automatic multipoint locking system with anti-panic function	Autotronic 834P Typ 4
18	Panic exit device	Automatic multipoint locking system with anti-panic function	Autotronic 834P Typ 4 Version 2-leaf
19	Panic exit device	Multipoint locking system with anti-panic function	Multisafe 870 Typ 8
20	Panic exit device	Multipoint locking system with anti-panic function	Multisafe 870 Typ 11 Multisafe 870 GL Typ 11
21	Panic exit device	Mortice lock with anti-panic function	Multisafe 871
22	Panic exit device	Electronic multipoint locking system with anti-panic function	Multitronic 881 Typ 8

First Issued: 2021-07-12

Effective Date: 2021-07-12

Latest Issue: 2021-07-12

Page: 5 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 746195

BS EN 1125:2008 - Building hardware – Panic exit devices operated by a horizontal bar, for use on escape routes.

Table 3: Product Information – Panic Exit Devices suitable for use on fire and smoke door assemblies (continued...)			
No	Description	Additional Information	Model
23	Panic exit device	Electronic multipoint locking system with anti-panic function	Multitronic 881 Typ 11 Multitronic 881 GL Typ 11
24	Panic exit device	Anti-panic conter box for inactive-leaf of aluminium steel, wood and plastic doors (x stands for backset / forend sizes dependent item number)	MPG xxx MPW xxx MPW xxx – mit Stangenversatz MPX xxx
Note	<i>Panic exit devices detailed in table 3 have conformed to the requirements of BS EN 1125:2008, Table 1: Performance characteristics and compliance criteria.</i>		

First Issued: 2021-07-12

Effective Date: 2021-07-12

Latest Issue: 2021-07-12

Page: 6 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 746195

Manufacturing Plant

Carl Fuhr GmbH & Co. KG
Carl-Fuhr-Str. 12
Heiligenhaus
Nordrhein-Westfalen
42579
Germany

Certified Activities

BS EN 1125:2008 – Autosafe, Autotronic, Multisafe and Multitronic Series Panic Exit Devices.
Mechanically operated by either a horizontal push-bar or a horizontal touch-bar, specifically designed for use in a panic situation on escape routes.



First Issued: 2021-07-12

Effective Date: 2021-07-12

Latest Issue: 2021-07-12

Page: 7 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.